

FM BROADCAST STATION LICENSE

Subject to the provisions of the Communications Act of 1934, as amended, treaties, and Commission Rules, and further subject to conditions set forth in this license, the LICENSEE

HARBENITO RADIO CORPORATION

is hereby authorized to use and operate the radio transmitting apparatus hereinafter described for the purpose of broadcasting for the term ending 3 a.m. Local Time: AUGUST 1, 1990

The licensee shall use and operate said apparatus only in accordance with the following terms:

1. Frequency (MHz): 101.9
 2. Transmitter output power: 24 kw
 3. Effective radiated power: 100 kw (H&V)
 4. Antenna height above
average terrain (feet): 670 feet (204 feet (H&V)
 5. Hours of operation: Unlimited
 6. Station location: San Antonio, Texas
 7. Main studio location: 1115 West Martin
San Antonio, Texas
 8. Remote Control point: 1115 West Martin
San Antonio, Texas
 9. Antenna & supporting structure: North Latitude: 29 ° 25 ' 08 "
West Longitude: 98 ° 29 ' 00 "
- CONTINENTAL G5CPS-8AC-3, 8 sections circularly polarized side mounted at the 710 feet (216 meters) level (C/R-AGL) on a 72 feet (22 meters) mast mounted on top of tower of the Americas. OVERALL HEIGHT ABOVE GROUND: 747 feet (228 meters) (without obstruction lighting)
10. Transmitter location: Tower of the Americas
San Antonio, Texas
 11. Transmitter(s) (See Sections 73.1660, 73.1665 and 73.1670 of Commission's Rules): Type Accepted
 12. Obstruction markings specifications in accordance with the following paragraphs of FCC Form 715: SEE PAGE 2.
 13. Conditions: --

The Commission reserves the right during said license period of terminating this license or making effective any changes or modification of this license which may be necessary to comply with any decision of the Commission rendered as a result of any hearing held under the rules of the Commission prior to the commencement of this license period or any decision rendered as a result of any such hearing which has been designated but not held, prior to the commencement of this license period.

This license is issued on the licensee's representation that the statements contained in licensee's application are true and that the undertakings therein contained so far as they are consistent herewith, will be carried out in good faith. The licensee shall, during the term of this license, render such broadcasting service as will serve public interest, convenience, or necessity to the full extent of the privileges herein conferred.

This license shall not vest in the licensee any right to operate the station nor any right in the use of the frequency designated in the license beyond the term hereof, nor in any other manner than authorized herein. Neither the license nor the right granted hereunder shall be assigned or otherwise transferred in violation of the Communications Act of 1934. This license is subject to the right of use or control by the Government of the United States conferred by section 606 of the Communications Act of 1934.

✓ This license consists of this page and pages

Dated: June 29, 1984
dac

FEDERAL
COMMUNICATIONS
COMMISSION



OBSTRUCTION MARKING AND LIGHTING SPECIFICATIONS
Inter-American Radio, Inc.
San Antonio, Texas

It is expressly understood that the issuance of these specifications is in no way to be considered as precluding additional or modified marking or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

PAINING

The 128-foot antenna supporting structure atop the Hemisfair Tower of the Americas shall be painted with 5 alternate bands of aviation surface orange and white terminating with aviation surface orange bands at both top and bottom. The bottom band shall be approximately 53 feet in width covering the 4-foot diameter solid section of the structure. The skeletal section of the structure shall be painted with four 18-foot wide alternate bands of aviation surface orange and white with the lower band being painted white and the top band orange.

LIGHTING

There shall be installed at the top of the antenna supporting structure one 300m/m electric code beacon equipped with two 500-, 620- or 700-watt lamps (PS-40, Code Beacon type), both lamps to burn simultaneously, and equipped with aviation red color filters. The beacon shall also be equipped with a flashing mechanism producing not more than 40 flashes per minute nor less than 12 flashes per minute with a period of darkness equal to approximately one-half of the luminous period.

All lights shall burn continuously or be controlled by a light sensitive control device adjusted so that the lights will be turned on at a north sky light intensity level of about 35 foot candles and turned off at a north sky light intensity level of about 58 foot candles.

TEMPORARY LIGHTS

During construction of the antenna structure, at least two 100-, 107 or 116-watt lamps (#100 A21/TS, #107 A21/TS or #116 A21/TS, respectively) enclosed in aviation red obstruction light globes, shall be installed at the uppermost point of the structure, and shall be displayed nightly from sunset to sunrise until the permanent obstruction lights have been installed and placed in operation, and shall be positioned so as to insure unobstructed visibility of at least one light from aircraft at any normal angle of approach.

THESE SPECIFICATIONS ARE A PART OF AND SHALL BE ATTACHED TO THE CURRENT INSTRUMENT OF AUTHORIZATION.