


# KNTH HOUSTON, TX BL-19830610AA 1070 kHz

Nighttime

Electric Field Strength  
at 1 km radius  
millivolts per meter - mV/m

Power: 5.0 kW  
Graph Maximum: 5000 mV/m



Facility ID: 61174  
Application ID: 58118  
CDBS Antenna System ID: 6879

9 Towers  
13 Augmentations  
Theoretical pattern RMS: 909.30

Azimuth	E <sub>theo</sub>	E <sub>std</sub>	E <sub>aug</sub>
0	7.19	28.81	107.71
5	6.89	28.73	100.45
10	4.26	28.16	95.97
15	0.68	27.81	96.50
20	2.08	27.89	101.18
25	2.71	27.95	108.64
30	1.09	27.83	115.48
35	1.47	27.85	119.41
40	2.68	27.95	120.70
45	0.16	27.80	118.05
50	8.36	29.15	113.79
55	22.67	36.60	111.55
60	41.36	51.56	113.76
65	61.00	69.83	120.68
70	77.01	85.50	128.97
75	84.54	93.02	133.53
80	79.86	88.35	128.95
85	61.77	70.56	116.41
90	32.89	44.34	115.05
95	1.15	27.83	112.16
100	22.16	36.26	105.84
105	18.71	34.04	99.45
110	30.46	42.38	99.19
115	143.79	153.51	165.28
120	335.01	352.86	353.03
125	608.77	639.82	639.82
130	957.43	1005.69	1005.69
135	1359.59	1427.84	1427.84
140	1781.32	1870.59	1870.59
145	2180.06	2289.23	2289.23
150	2510.90	2636.59	2636.59
155	2733.87	2870.70	2870.70
160	2820.97	2962.15	2962.15
165	2761.21	2899.40	2899.40
170	2562.56	2690.83	2690.83
175	2250.49	2363.18	2363.18

The theoretical pattern is used to create the standard pattern. Augmentations (if any) expand the standard pattern in specified directions. See Sections 73.150 and 73.152 of the FCC's Rules.

AM coverage may not mirror the pattern shown here. Additional factors such as ground conductivity or skywave propagation affect how far the AM signal will travel.

Patterns for stations outside the USA are based on notified parameters.

AM directional patterns created before 1982 used units of 1 mV/m at 1 mile, not one kilometer. The pattern values on such plots at 1 mile will be 0.62137 of the values listed here. Measured pattern values may vary from values shown here.

Plot is best printed on 11" by 17" or larger paper.

13 Nov 2009

Prepared by Audio Division, Media Bureau  
Federal Communications Commission

Azimuth	E <sub>theo</sub>	E <sub>std</sub>	E <sub>aug</sub>
180	1863.27	1956.63	1956.63
185	1445.20	1517.71	1517.71
190	1039.25	1091.57	1091.57
195	680.70	715.27	715.27
200	392.81	413.39	413.39
205	185.34	196.59	199.69
210	55.61	64.68	93.02
215	8.55	29.22	81.55
220	24.42	37.82	85.03
225	10.98	30.10	85.39
230	15.04	31.98	94.74
235	40.62	50.91	103.38
240	57.90	66.85	113.56
245	63.70	72.43	119.10
250	58.65	67.56	113.98
255	45.95	55.69	100.64
260	29.96	41.99	86.04
265	14.88	31.89	74.13
270	3.76	28.08	62.94
275	2.05	27.89	52.14
280	2.94	27.97	45.73
285	0.75	27.81	41.97
290	2.12	27.89	41.90
295	3.53	28.05	42.09
300	2.47	27.92	45.14
305	0.74	27.81	49.72
310	4.62	28.22	55.75
315	7.32	28.84	66.58
320	7.52	28.90	79.94
325	5.10	28.32	92.21
330	1.23	27.83	102.91
335	2.23	27.90	112.06
340	3.59	28.06	118.54
345	2.21	27.90	120.70
350	1.20	27.83	118.49
355	4.95	28.28	113.63